

WHAT IS CLAIMED IS:

1. A chair with pivotable back comprising:

a seat which is adapted to support buttocks of a human user, said seat having a first side edge and a second side edge;

5 a first armrest secured to said seat and mounted at said first side edge;

a second armrest secured to said seat and mounted at said second side edge;

10 a chair back which is adapted to be located against the user's back;

a first pivot pin interconnecting said first armrest and said chair back;

15 a second pivot pin interconnecting said second armrest and said chair back, whereby said chair back is capable of pivoting relative to said seat between and upright or transverse position relative to said seat and a collapsed position locating said chair back in juxtaposition with said seat; and

20 said first armrest having a first pin lock assembly, said second armrest having a second pin lock assembly, both said first pin lock assembly and said second pin lock assembly securely engaging with said chair back to fix same in place when said chair back is in said upright position.

2. The chair with pivotable back as defined in Claim 1 wherein:

said chair back having a first hole and a second hole, said first pin lock assembly engaging with said first hole, said second pin lock assembly engaging with said second hole.

3. The chair with pivotable back as defined in Claim 2 wherein:

said chair back including a first cam surface located directly adjacent said first hole, said chair back including a second cam surface located directly adjacent said second hole, whereby during movement of said chair back from said collapsed position to said upright position said first pin lock assembly is depressed to a retracted position by said first cam surface and said second pin lock assembly is moved to a retracted position by said second cam surface and upon said first pin lock assembly and said second pin lock assembly reaching respectively said first hole and said second hole said first pin lock assembly and said second pin lock assembly each move to an extended position.

4. The chair with pivotable back as defined in Claim 3 wherein:

said first pin lock and said second pin lock being continuously spring biased toward said extended position.